

Self-Service Open Multi-Deck Merchandiser w/ Service Dome (RRS Optional)

PTD-RG REMOTE BASE & REMOTE GRAVITY DOME - 4', 6', 8', 10' & 12'

Electrical Data (Dome)

Model		Fans per Case	Box Fans		High Efficiency Fans		Anti-Condensate Fans		Drain Heaters		Optional Defrost Heaters	
			120 Volts		120 Volts		120 Volts		120 Volts		208 Volts	
			Amps	Watts	Amps	Watts	Amps	Watts	Amps	Watts	Amps	Watts
PTD-RG	4'	1	0.13	15.6	---	---	0.17	20.4	---	---	---	---
	6'	2	0.26	31.2	---	---	0.31	37.2	---	---	---	---
	8'	3	0.39	46.8	---	---	0.42	50.4	---	---	---	---
	10'	4	0.52	62.4	---	---	0.52	62.4	---	---	---	---
	12'	4	0.52	62.4	---	---	0.62	74.4	---	---	---	---

Electrical Data (Base)

Model		Fans per Case	High Efficiency Fans		Anti-Condensate Fans		Drain Heaters		Optional Defrost Heaters		RRS ²		
			120 Volts		120 Volts		120 Volts		208 Volts		Fans per Case	Unit Cooler Fans	
			120 Volts		120 Volts		120 Volts		208 Volts			120 Volts	
			Amps	Watts	Amps	Watts	Amps	Watts	Amps	Watts		Amps	Watts
PTD-RG	4'	1	0.3	36	---	---	---	---	---	---	---	---	---
	6'	2	0.6	72	---	---	---	---	---	---	---	---	---
	8'	3	0.9	108	---	---	---	---	---	---	---	---	---
	10'	4	1.2	144	---	---	---	---	---	---	---	---	---
	12'	4	1.2	144	---	---	---	---	---	---	---	---	---

Lighting Data

Model		Lights per Row	Light Length (ft)	Clearvoyant 4 LED Lighting (Per Light Row)			
				Standard Power (Cornice or Shelf)		High Power (Cornice)	
				120 Volts		120 Volts	
				Amps	Watts	Amps	Watts
PTD-RG	4'	1	4	0.05	5.9	0.12	14.9
	6'	2	3	0.08	9.4	0.20	23.8
	8'	2	4	0.10	11.8	0.24	29.8
	10'	2	5	0.12	15.0	0.30	37.0
	12'	3	4	0.15	17.7	0.36	44.7

Guidelines & Control Settings (DX)

Model		Conventional ³ BTUH/ft	Parallel ⁴ BTUH/ft	Superheat Set Point @ Bulb (°F)	Evaporator (°F)	Discharge Air (°F)	Discharge Air ⁵ Velocity (FPM)
PTD-RG	Dome	330	300	6-8	15	28	---
	Base	485	445	6-8	26	29	250
	RRS	109	100	10	26	29	200

Engineered for stores with ambient conditions not to exceed 75° and 55% relative humidity.

Due to engineering improvements specifications may change without notice.

All measurements are taken per ASHRAE - 72 - 2005 specifications.

Hillphoenix refrigerated display cases for sale in the United States meet or exceed department of energy 2017 efficiency requirements.

Numbers are based on standard case sizes. Consult engineering.



(Remote Base/Remote Gravity Dome)

Defrost Controls

Model		Defrosts per Day	Run-Off Time (min)	Electric Defrost		Timed-Off Defrost		Hot Gas Defrost	
				Fail-Safe (min)	Termination Temp (°F)	Fail-Safe (min)	Termination Temp (°F)	Fail-Safe (min)	Termination Temp (°F)
PTD-RG	Dome	1	---	---	---	90/60	47	---	---
	Base	4	---	---	---	65/ ⁶ 36	42	---	---
	RRS	4	---	---	---	65/ ⁷ 36	42	---	---

- 1 NOTE: " - - - " indicates data not applicable.
- 2 RRS - Refrigerated Rear Storage.
- 3,4 Listed BTUH indicates unlighted shelves. Add the following for lighted shelves:
 - 4' Shelf LED: 36 BTUH
 - 4' Canopy LED: 72 BTUH
 - 3' Shelf LED: 27 BTUH
 - 3' Hi-Output LED: 54 BTUH
- 5 Average discharge air velocity at peak of defrost.
- 6,7 Time-off duration for defrost with no termination control.

SERVICE/Self-SERVICE MULTI-DECK

Beverage / Deli / Meat / Seafood



Engineered for stores with ambient conditions not to exceed 75° and 55% relative humidity. Due to engineering improvements specifications may change without notice. All measurements are taken per ASHRAE - 72 - 2005 specifications. Hillphoenix refrigerated display cases for sale in the United States meet or exceed department of energy 2017 efficiency requirements. Numbers are based on standard case sizes. Consult engineering.



(Remote Base/Remote Gravity Dome)

