


GENERAL NOTES:

- "----" Indicates that the feature is not an option on this case model and/or the data is not yet available at this time.



SHIPPING WEIGHT	
Case	Weight
NFT-R	---



ENGINEERED FOR STORES WITH AMBIENT CONDITIONS NOT TO EXCEED 75° AND 55% RELATIVE HUMIDITY. DUE TO ENGINEERING IMPROVEMENTS SPECIFICATIONS MAY CHANGE WITHOUT NOTICE. ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS. NUMBERS ARE BASED ON STANDARD CASE SIZES. CONSULT ENGINEERING.

NFT-R

Rev. Date	Rev. #	Rev. Title
05-03-21	1	NEW STANDARDS



ELECTRICAL DATA (TOP)

	Fans Per Case	High Efficiency Fans		Anti-Condensate Fans		Drain Heaters		Optional Defrost Heaters	
		120 Volts		120 Volts		120 Volts		208 Volts	
		Amps	Watts	Amps	Watts	Amps	Watts	Amps	Watts
2 Door	1	0.26	31.2	---	---	---	---	---	---
3 Door	2	0.52	62.4	---	---	---	---	---	---
4 Door	2	0.52	62.4	---	---	---	---	---	---
5 Door	3	0.78	93.6	---	---	---	---	---	---
6 Door	4	1.04	124.8	---	---	---	---	---	---

ELECTRICAL DATA (BASE)

	Fans Per Case	High Efficiency Fans		Anti-Condensate Fans		Drain Heaters		Optional Defrost Heaters	
		120 Volts		120 Volts		120 Volts		208 Volts	
		Amps	Watts	Amps	Watts	Amps	Watts	Amps	Watts
2 Door	1	0.30	36.0	---	---	---	---	---	---
3 Door	2	0.60	72.0	---	---	---	---	---	---
4 Door	2	0.60	72.0	---	---	---	---	---	---
5 Door	5	1.50	180.0	---	---	---	---	---	---
6 Door	6	1.80	216.0	---	---	---	---	---	---

LIGHTING DATA

	Lights Per Row	Light Length	Clearvoyant 4 LED Lighting (Per Light Row)			
			Standard Power (Cornice or Shelf)		High Power (Cornice)	
			120 Volts		120 Volts	
			Amps	Watts	Amps	Watts
2 Door	1	4'	0.05	5.9	0.12	14.9
3 Door	2	3'	0.08	9.4	0.20	23.8
4 Door	2	4'	0.10	11.8	0.24	29.8
5 Door	2	5'	0.12	15.0	0.30	37.0
6 Door	3	4'	0.15	17.7	0.36	44.7

NOTES:

- "—" Indicates that the feature is not an option on this case model and/or the data is not yet available at this time.
- Listed BTUH indicates unlighted shelves. Add the following for lighted shelves:
 - 4' Shelf LED: 36 BTUH
 - 4' Canopy LED: 72 BTUH
 - 3' Shelf LED: 27 BTUH
 - 3' Hi-Output LED: 54 BTUH
- Listed discharge air velocity represents the average velocity at the peak of defrost.



ENGINEERED FOR STORES WITH AMBIENT CONDITIONS NOT TO EXCEED 75° AND 55% RELATIVE HUMIDITY. DUE TO ENGINEERING IMPROVEMENTS SPECIFICATIONS MAY CHANGE WITHOUT NOTICE. ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS. NUMBERS ARE BASED ON STANDARD CASE SIZES. CONSULT ENGINEERING.

NFT-R

Rev. Date	Rev. #	Rev. Title
05-03-21	1	NEW STANDARDS



A DOVER COMPANY

GUIDELINES AND CONTROL SETTINGS (DX)

	BTUH/ft		Superheat Set Point @ Bulb (°F)	Evaporator (°F)	Discharge Air (°F)	Discharge Air Velocity (FPM)
	Conventional	Parallel				
Top	382	350	8 - 10	35	32	250
Base	872	800	8 - 10	35	32	250

DEFROST CONTROLS

	Defrosts Per Day	Run-Off Time (Min)	Electric Defrost		Timed-Off Defrost		Hot Gas Defrost	
			Fail-Safe (Min)	Termination Temp (°F)	Fail-Safe (Min)	Termination Temp (°F)	Fail-Safe (Min)	Termination Temp (°F)
Top	6	---	---	---	20	---	---	---
Base	6	---	---	---	20	---	---	---




ENGINEERED FOR STORES WITH AMBIENT CONDITIONS NOT TO EXCEED 75° AND 55% RELATIVE HUMIDITY. DUE TO ENGINEERING IMPROVEMENTS SPECIFICATIONS MAY CHANGE WITHOUT NOTICE. ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS. NUMBERS ARE BASED ON STANDARD CASE SIZES. CONSULT ENGINEERING.

NFT-R

Rev. Date	Rev. #	Rev. Title
05-03-21	1	NEW STANDARDS



Self-Service Open Multi-Deck Open/Door Combination Vase/Bouquet Merchandiser
2, 3, 4, 5 & 6 Door (Floral)



NFT-R

Clearv^oyant™
LED SYSTEM

Hillphoenix.

A DOVER COMPANY