




GENERAL NOTES

- “---” indicates that the feature is not an option on this case model and/or the data is not yet available.
- LED lights only.



SHIPPING WEIGHT	
Case	Weight
O3IMQA	---



ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

O3IMQA

Rev. Date	Rev. #	Rev. Title
8-10-20	1	SOLOCHILL V5
3-16-20	0	SOLOCHILL V4



ELECTRICAL DATA									
Case Length	Fans Per Case	High Efficiency Fans		Anti Condensate Heaters		Defrost Heaters			
		120 Volt		120 Volts		208 Volts		240 Volts	
		Amps	Watts	Amps	Watts	Amps	Watts	Amps	Watts
8'	6	0.46	27.6	0.67	80.0	7.70	1600	8.88	2130
12'	8	0.62	36.8	1.06	127.0	11.54	2400	13.32	3200

DEFROST CONTROLS					
Defrosts Per Day	Run Off Time (Min)	Electric Defrost		Timed-Off Defrost	
		Fail Safe (Min)	Termination Temp (°F)	Fail-Safe (Min)	Termination Temp (°F)
4	6 - 8	30	47	45	45

NOTES

- "—" indicates that the feature is not an option on this case model and/or the data is not yet available.
- Listed discharge air velocity represents the average velocity at the peak of defrost.
- Temperature and defrost settings listed above are recommended start-up settings. Final operational settings may need to be adjusted for the store conditions in which the case operates.



ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

O3IMQA

Rev. Date	Rev. #	Rev. Title
8-10-20	1	SOLOCHILL V5
3-16-20	0	SOLOCHILL V4

O3IMQA

8' & 12' Medium Temp Island Merchandiser
Deli / Meat

SOLOCHILL
MICRO-DISTRIBUTED

SOLOCHILL DATA			@95° Condensing Temperature			
Volts	Phase	Frequency	Wire			
208	1	60	3 Wire + Ground			
Application			Case Length	Evaporator Temp (°F)	Discharge Air (°F)	Discharge Air Velocity (FPM)
Meat			8'	15	26	270
Meat			12'	15	26	270
Deli			8'	20	30	270
Deli			12'	20	30	270

Application	Case Length	R448A					
		Condensing Unit Model	MCA	MOP	Required Capacity	THR (BTUH)	Flow Rate
Meat	8'	DA330	26.1	30	13400	17460	5.0
Meat	12'	DA420	35.6	40	20100	25777	7.4
Deli	8'	DA330	25.1	30	12248	15657	4.5
Deli	12'	DA420	35.6	40	18372	23192	6.6



ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

O3IMQA

Rev. Date	Rev. #	Rev. Title
8-10-20	1	SOLOCHILL V5
3-16-20	0	SOLOCHILL V4

Hillphoenix
A DOVER COMPANY



FRONT OPTIONS		
<div>ANGLED THERMOPANE</div>	<div>8.75" CURVED PLEXI</div>	<div>5.5" CURVED PLEXI</div>
CENTER TOWER OPTIONS		
<div>31" LIGHTED TOWER</div>	<div>24" TOWER</div>	




ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

O3IMQA

Rev. Date	Rev. #	Rev. Title
8-10-20	1	SOLOCHILL V5
3-16-20	0	SOLOCHILL V4





NOTES

** : STUB-UP AREA

① : AVAILABLE SHELF SIZES: 10" , 12" , 14" , 16"

- Front and center sill heights vary with base frame height.



ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

O3IMQA

Rev. Date	Rev. #	Rev. Title
8-10-20	1	SOLOCHILL V5
3-16-20	0	SOLOCHILL V4