




**GENERAL NOTES:**

- "----" Indicates that the feature is not an option on this case model and/or the data is not yet available at this time.



SHIPPING WEIGHT	
Case	Weight
HSC-SC	---

**HSC-SC**

Rev. Date	Rev. #	Rev. Title
02-04-21	1	NEW STANDARDS



## SYSTEM REQUIREMENTS

Case Length	Volts	Phase	Total Amps	Minimum Circuit Ampacity	Maximum Overcurrent Protection
2'	120	1	4.75	5.7	15
4'	120	1	7.47	9.0	15
6'	120	1	12.46	13.8	20

## SYSTEM REQUIREMENTS

Case Length	Volts	Phase	Total Amps	Minimum Circuit Ampacity	Maximum Overcurrent Protection
2'	120/208	1	3.90	4.9	15
4'	120/208	1	6.10	7.6	15
6'	120/208	1	6.43	7.8	15

## ELECTRICAL DATA

Case Length	Fans Per Case	High Efficiency Fans		Anti-Condensate Fans		Drain Pumps	
		120 Volts		120 Volts		120 Volts	
		Amps	Watts	Amps	Watts	Amps	Watts
2'	1	0.30	25	---	---	---	---
4'	2	0.60	50	---	---	---	---
6'	2	0.60	50	---	---	---	---

## LIGHTING DATA

Case Length	Lights Per Row	Light Length	Clearvoyant 4 LED Lighting (Per Light Row)			
			Standard Power (Cornice or Shelf)		High Power (Cornice)	
			120 Volts		120 Volts	
			Amps	Watts	Amps	Watts
2'	1	2'	0.03	3.1	0.06	7.8
4'	1	4'	0.05	5.9	0.12	14.9
6'	2	3'	0.08	9.4	0.20	23.8

## GUIDELINES AND CONTROL SETTINGS

Case Length	24hr Energy Usage (kWh/ft)	Discharge Air (°F)	Discharge Air Velocity (FPM)
2'	6.17	28 - 30	203
4'	12.31	28 - 30	184
6'	15.39	28 - 30	158

## NOTES:

- "---" Indicates that the feature is not an option on this case model and/or the data is not yet available at this time.
- Listed discharge air velocity represents the average velocity at the peak of defrost.
- RLA - Running Load Amps
- LRA - Locked Rotor Amps



## HSC-SC



ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

Rev. Date	Rev. #	Rev. Title
02-04-21	1	NEW STANDARDS



CONDENSING UNIT DATA										
Case Length	Volts	Phase	BTUHs	RLA (Amps)	LRA (Amps)	Qty	Refrig.	Grams	Condenser Fans	
									Amps	Watts
2'	120	1	2054	3.9	25.1	1	R290	84	0.43	25
4'	120	1	4495	6.1	42.0	1	R290	138	0.53	30
6'	120	1	2734	5.3	32.0	2	R290	142	0.43	25

DEFROST CONTROLS							
Defrosts Per Day	Run-Off Time (Min)	Electric Defrost		Timed-Off Defrost		Hot Gas Defrost	
		Fail-Safe (Min)	Termination Temp (°F)	Fail Safe (Min)	Termination Temp (°F)	Fail-Safe (Min)	Termination Temp (°F)
6	---	---	---	30	45	---	---





ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

## HSC-SC

Rev. Date	Rev. #	Rev. Title
02-04-21	1	NEW STANDARDS





## HSC-SC



ALL MEASUREMENTS ARE TAKEN PER ASHRAE-72-2005 SPECIFICATIONS. HILLPHOENIX REFRIGERATED DISPLAY CASES FOR SALE IN THE UNITED STATES MEET OR EXCEED DEPARTMENT OF ENERGY 2017 REQUIREMENTS.

Rev. Date	Rev. #	Rev. Title
02-04-21	1	NEW STANDARDS